



PRZEDSIĘBIORSTWO PRODUKCYJNE
 PODZESPOŁÓW ELEKTRONICZNYCH
DOLAM S.A.

50-425 Wrocław, ul. Krakowska 64, Poland
 tel. (+48) 71/342-65-54, fax (+48) 71/342-58-59
 e-mail: sales@dolam.pl
 www.dolam.pl

Signal relays for telephone exchanges,
 system E-10
K-110
 form A contact (normally open)
 for PCBs

This product is in accordance with RoHs

PARAMETERS	Unit	TYPE	
		K-110/3x1	K-110/1x1

1.CONTACT PARAMETERS

Switching power	max	W	10	12
Breakdown voltage	min	V _{DC}	400	
Switching voltage	max	V _{DC}	200	
Switching current	max	A	0.5	
Contact resistance	max	m	200	
Contact-contact capacitance	max	pF	1.5	

2.COIL PARAMETERS

Coil normal working voltage		V _{DC}	12*	4
Pull-in voltage	max	V _{DC}	9	3.5
Drop-out voltage	min	V _{DC}	1	0.3
Nominal coil resistance	±10%		200	275

3.RELAY PARAMETERS

Insulation resistance	min		10 ⁹	
Operate time including bounces	max	ms	1.5	
Release time	max	ms	1	
Breakdown voltage coil-contact	min	V _{DC}	700	
Environment category acc. to IEC 68-2-1+3			40/70/10	40/70/21

*Switching on voltage 12V, working voltage 6V

4.DIMENSIONS AND TERMINAL ARRANGEMENTS

